



# 49293 BLUE RTV SILICONE GASKET MAKER - L/V

Nov 14 2014 11:30 PM

## Safety Data Sheet

**Supply Co. - 49293 BLUE RTV SILICONE GASKET MAKER - L/V**

Document Nbr: 067677  
Class C Parts IDs 21510,21511

MSDS DOCUMENT

PRINT REV. DATE: 12/13/2012

PRODUCT: DYNATEX(R\*) 49293 BLUE RTV SILICONE GASKET MAKER - L/V

-----1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION -----

TRADE NAME OF THIS PRODUCT:

DYNATEX(R\*) 49293 BLUE RTV SILICONE GASKET MAKER - L/V

MSDS ID: DYN49293

MANUFACTURER:

DYNATEX INC.

350 RING ROAD

ELIZABETHTOWN, KY 42701

PHONE NUMBER: (270) 769-3385

EMERGENCY PHONE:

CHEMTREC: (800) 424-9300

REVISION DATE: 12/13/2012

NFPA:

HEALTH 2

FIRE 1

REACTIVITY 0

SPECIFIC

-----2. COMPOSITION AND INFORMATION ON INGREDIENTS -----

INGREDIENT	CAS NUMBER	WEIGHT %	ACGIH TLV	PEL	STEL
METHYLTRACETOXY-	4253-34-3	1% - 5%	TWA: 10 PPM	TWA: 10 PPM	15 PPM
SILANE					

ETHYLTRiacETOXY- 17689-77-9 1% - 5% TWA: 10 PPM TWA: 10 PPM 15 PPM

SILANE

-----3. HAZARD IDENTIFICATION -----

EYE CONTACT: DIRECT CONTACT MAY CAUSE MODERATE IRRITATION.

SKIN CONTACT: MAY CAUSE MODERATE IRRITATION.

INHALATION:

MATERIAL IS NOT LIKELY TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITIONS. HOWEVER, IF MATERIAL IS HEATED OR HIGH VAPOR/AEROSOL CONCENTRATIONS ARE ATTAINED, CENTRAL NERVOUS SYSTEM DEPRESSION MAY OCCUR, WHICH IS CHARACTERIZED BY DROWSINESS, DIZZINESS, CONFUSION OR LOSS OF COORDINATION.

INGESTION:

LOW INGESTION HAZARD IN NORMAL USE. REPEATED INGESTION OR SWALLOWING LARGE AMOUNTS MAY INJURE INTERNALLY.

SYMPTOMS OF OVEREXPOSURE: NO KNOWN APPLICABLE INFORMATION.

EXISTING CONDITIONS AGGRAVATED BY EXPOSURE: NO KNOWN APPLICABLE INFORMATION.

NOTE:

THE ABOVE LISTED POTENTIAL EFFECTS OF OVEREXPOSURE ARE BASED ON ACTUAL DATA, RESULTS OF STUDIES PERFORMED UPON SIMILAR COMPOSITIONS, COMPONENT DATA AND/OR EXPERT REVIEW OF THE PRODUCT. PLEASE REFER TO SECTION 11 FOR THE DETAILED TOXICOLOGY INFORMATION.

-----4. FIRST AID INFORMATION -----

EYE CONTACT:

IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION.

SKIN CONTACT:

REMOVE FROM SKIN AND WASH THOROUGHLY WITH SOAP AND WATER OR WATERLESS CLEANSER. GET MEDICAL ATTENTION IF IRRITATION OR OTHER ILL EFFECTS DEVELOP OR PERSIST.

INHALATION:

MATERIAL IS NOT LIKELY TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITIONS. IF MATERIAL IS HEATED OR VAPOR ARE GENERATED, CARE SHOULD BE

TAKEN TO PREVENT INHALATION. IN CASE OF EXPOSURE TO VAPOR, MOVE TO FRESH AIR.

INGESTION: DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

COMMENTS: TREAT ACCORDING TO PERSON'S CONDITION AND SPECIFICS OF EXPOSURE.

-----5. FIRE FIGHTING MEASURES -----

FLASH POINT: >212F / >100C

FP METHOD: CLOSED CUP

AUTO-IGNITION TEMPERATURE: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR: NOT DETERMINED

EXTINGUISHING MEDIA:

ON LARGE FIRES USE DRY CHEMICAL, FOAM, OR WATER SPRAY. ON SMALL FIRES USE CARBON DIOXIDE, DRY CHEMICAL OR WATER SPRAY. WATER CAN BE USED TO COOL FIRE EXPOSED CONTAINERS.

SPECIAL FIRE FIGHTING PROCEDURES:

SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN WHEN FIGHTING LARGE FIRES INVOLVING CHEMICALS. DETERMINE THE NEED TO EVACUATE OR ISOLATE THE AREA ACCORDING TO YOUR LOCAL EMERGENCY PLAN. USE WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL BREAKDOWN OF THIS PRODUCT DURING FIRE OR VERY HIGH HEAT CONDITIONS MAY EVOLVE THE FOLLOWING HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON OXIDES AND TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS:

FORMALDEHYDE

SILICON DIOXIDE

NITROGEN OXIDES

METAL OXIDES

SULFUR OXIDES

CHLORINE COMPOUNDS

COMMENT:

WHEN TEMPERATURES ABOVE 150 DEG. C IN THE PRESENCE OF AIR, PRODUCT CAN FORM FORMALDEHYDE VAPORS. FORMALDEHYDE IS A POTENTIAL CANCER HAZARD, A KNOWN SKIN AND RESPIRATORY SENSITIZER, AND AN IRRITANT TO THE EYES, NOSE, THROAT, SKIN

AND DIGESTIVE SYSTEM. SAFE HANDLING CONDITIONS MAY BE MAINTAINED BY KEEPING VAPOR CONCENTRATIONS WITHIN THE OSHA PERMISSIBLE EXPOSURE LIMITS FOR FORMALDEHYDE.

-----6. ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IN CASE OF SPILL OR RELEASE:

OBSERVE ALL PERSONAL PROTECTION EQUIPMENT RECOMMENDATIONS. WIPE UP OR SCRAPE UP AND CONTAIN FOR SALVAGE OR DISPOSAL. CLEAN AREA AS APPROPRIATE SINCE SPILLED MATERIALS, EVEN IN SMALL QUANTITIES, MAY PRESENT A SLIP HAZARD. FINAL CLEANING MAY REQUIRE STEAM, SOLVENTS OR DETERGENTS. DISPOSE OF SATURATED ABSORBANT OR CLEANING MATERIALS APPROPRIATELY, SINCE SPONTANEOUS HEATING MAY OCCUR.

LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS MAY APPLY TO RELEASES AND DISPOSAL OF THIS MATERIAL, AS WELL AS THOSE MATERIALS AND ITEMS EMPLOYED IN THE CLEANUP OF RELEASES. YOU WILL NEED TO DETERMINE WHICH FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS ARE APPLICABLE. SECTIONS 13 AND 15 OF THIS MSDS PROVIDE INFORMATION REGARDING CERTAIN FEDERAL AND STATE REQUIREMENTS.

-----7. HANDLING AND STORAGE -----

HANDLING:

USE WITH ADEQUATE VENTILATION. PRODUCT EVOLVES ACETIC ACID WITH EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL ACETIC ACID WITH EXPOSURE GUIDELINES OR USE RESPIRATORY PROTECTION. AVOID EYE CONTACT. AVOID SKIN CONTACT. DO NOT TAKE INTERNALLY. AVOID BREATHING VAPOR. KEEP CONTAINER CLOSED.

STORAGE:

USE REASONABLE CARE AND STORE AWAY FROM OXIDIZING MATERIALS. KEEP CONTAINER CLOSED AND STORE AWAY FROM WATER OR MOISTURE. THIS MATERIAL IN ITS FINELY DIVIDED FORM PRESENTS AN EXPLOSION HAZARD. FOLLOW NFPA 654 (FOR CHEMICAL DUSTS) OR 484 (FOR METAL DUSTS) AS APPROPRIATE FOR MANAGING DUST HAZARDS TO MINIMIZE SECONDARY EXPLOSION POTENTIAL.

-----8. EXPOSURE CONTROLS AND PERSONAL PROTECTION -----

COMPONENT EXPOSURE LIMITS:

COMPONENT NAME: HYDROTREATED MIDDLE PETROLEUM DISTILLATES

CAS NUMBER: 64742-46-7

EXPOSURE LIMITS:



OSHA PEL (FINAL RULE) AND ACGIH TLV FOR OIL MISTS: TWA 5 MG/M3

COMPONENT NAME: ETHYLTRiacETOXYSILANE

CAS NUMBER: 17689-77-9

EXPOSURE LIMITS: SEE ACETIC ACID COMMENTS

COMPONENT NAME: METHYLTRiacETOXYSILANE

CAS NUMBER: 4253-34-3

EXPOSURE LIMITS: SEE ACETIC ACID COMMENTS

ACETIC ACID IS FORMED UPON CONTACT WITH WATER OR HUMID AIR.

ENGINEERING CONTROLS:

LOCAL VENTILATION: RECOMMENDED

GENERAL VENTILATION: RECOMMENDED

EYE PROTECTION:

USE PROPER PROTECTION - SAFETY GLASSES AS A MINIMUM.

SKIN PROTECTION:

WASH AT MEALTIMES AND END OF SHIFT. CONTAMINATED CLOTHING AND SHOES SHOULD

BE REMOVED AS SOON AS PRACTICAL AND THOROUGHLY CLEANED BEFORE REUSE. CHEMICAL

PROTECTIVE GLOVES ARE RECOMMENDED.

SUITABLE GLOVES:

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES.

RESPIRATORY PROTECTION:

USE RESPIRATORY PROTECTION UNLESS ADEQUATE EXHAUST VENTILATION IS PROVIDED OR EXPOSURE ASSESSMENT DEMONSTRATES THAT EXPOSURES ARE WITHIN EXPOSURE GUIDELINES. INDUSTRIAL HYGIENE PERSONNEL CAN ASSIST IN JUDGING THE ADEQUACY OF EXISTING ENGINEERING CONTROLS.

SUITABLE RESPIRATOR:

RESPIRATORY PROTECTION IS NOT NEEDED UNDER AMBIENT CONDITIONS. IF VAPOR IS GENERATED WHEN MATERIAL IS HEATED OR HANDLED, THE FOLLOWING IS ADVISED. GENERAL AND LOCAL EXHAUST VENTILATION IS RECOMMENDED TO MAINTAIN VAPOR EXPOSURES BELOW RECOMMENDED LIMITS. WHERE CONCENTRATIONS ARE ABOVE RECOMMENDED LIMITS OR ARE UNKNOWN, APPROPRIATE RESPIRATORY PROTECTION SHOULD BE WORN. FOLLOW OSHA RESPIRATOR REGULATIONS (29 CFR 1910.134) AND USE NIOSH/MSHA APPROVED RESPIRATORS.

PRECAUTIONARY MEASURES:

AVOID EYE CONTACT. AVOID SKIN CONTACT. AVOID BREATHING VAPOR. KEEP CONTAINER CLOSED. DO NOT TAKE INTERNALLY. USE REASONABLE CARE.

COMMENT:

PRODUCT EVOLVES ACETIC ACID WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL ACETIC ACID WITHIN EXPOSURE GUIDELINES OR USE RESPIRATORY PROTECTION.

WHEN HEATED TO TEMPERATURES ABOVE 150C (300F) IN THE PRESENCE OF AIR, PRODUCT CAN FORM FORMALDEHYDE VAPORS. PHYSICAL AND HEALTH HAZARD INFORMATION IS READILY AVAILABLE ON THE MATERIAL SAFETY DATA SHEET.

NOTE:

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED TEMPERATURES OR AEROSOL/SPRAY APPLICATIONS MAY REQUIRE ADDED PRECAUTIONS.

-----9. PHYSICAL AND CHEMICAL PROPERTIES -----

PHYSICAL STATE: PASTE

SPECIFIC GRAVITY: 1.007

COLOR/APPEARANCE: BLUE

ODOR: ACETIC ACID ODOR

PH: NOT DETERMINED

BOILING/COND. POINT: NOT DETERMINED

MELTING/FREEZING POINT: NOT DETERMINED

SOLUBILITY: NOT DETERMINED

EVAPORATION RATE: NOT DETERMINED

VOC %: 30 G/L

VISCOSITY: NOT DETERMINED

VAPOR DENSITY: NOT DETERMINED

VAPOR PRESSURE: NOT DETERMINED

NOTE:

THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT

SPECIFICATIONS. CONTACT ACCUMETRIC LLC BEFORE WRITING SPECIFICATIONS.

-----10. STABILITY AND REACTIVITY -----

CHEMICAL STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE KNOWN

MATERIALS TO AVOID / INCOMPATIBILITY:

OXIDIZING MATERIAL CAN CAUSE A REACTION. WATER, MOISTURE OR HUMID AIR CAN  
CAUSE HAZARDOUS VAPORS TO FORM AS DESCRIBED IN SECTION 8.

-----11. TOXICOLOGICAL INFORMATION -----

COMPONENT TOXICOLOGY INFORMATION:

INHALATION OF FUMES MAY RESULT IN METAL FUME FEVER, A FLU-LIKE ILLNESS WITH  
SYMPTOMS OF METALLIC TASTE, FEVER AND CHILLS, ACHES, CHEST TIGHTNESS AND  
COUGH.

SPECIAL HAZARD INFORMATION ON COMPONENTS: NO KNOWN APPLICABLE INFORMATION.

-----12. ECOLOGICAL INFORMATION -----

ENVIRONMENTAL FATE AND DISTRIBUTION:

COMPLETE INFORMATION IS NOT YET AVAILABLE.

ENVIRONMENTAL EFFECTS: COMPLETE INFORMATION IS NOT YET AVAILABLE.

FATE AND EFFECTS IN WASTE WATER TREATMENT PLANTS:

COMPLETE INFORMATION IS NOT YET AVAILABLE.

-----13. DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD:

WE MAKE NO GUARANTEE OR WARRANTY OF ANY KIND THAT THE USE OR DISPOSAL OF THIS PRODUCT COMPLIES WITH ALL LOCAL, STATE, OR FEDERAL LAWS. IT IS ALSO THE OBLIGATION OF EACH USER OF THE PRODUCT MENTIONED HEREIN TO DETERMINE AND COMPLY WITH THE REQUIREMENTS OF ALL APPLICABLE STATUTES.

THIS PRODUCT IS NOT KNOWN TO BE REGULATED UNDER RCRA REGULATIONS, BUT CONTAINS SARA REGULATED SUBSTANCES. DISPOSAL OF UNUSED PORTIONS OF THIS PRODUCT AND PROCESS WASTE CONTAINING THIS PRODUCT SHOULD BE DONE ONLY AFTER

A CAREFUL EVALUATION AND IN COMPLIANCE WITH ALL FEDERAL, LOCAL AND STATE LAWS.

-----14. TRANSPORTATION INFORMATION -----

VOIE TERRESTRE DOT: PAS ASSUJETTI AU DOT

OCEAN SHIPMENT (IMDG): NOT SUBJECT TO IMDG CODE.

AIR SHIPMENT (IATA): NOT SUBJECT TO IATA REGULATIONS.

-----15. REGULATORY INFORMATION -----

THE CONTENTS OF THIS MSDS COMPLY WITH THE OSHA HAZARD COMMUNICATION STANDARD  
29 CFR 1910.1200.

TSCA STATUS:

ALL CHEMICAL SUBSTANCES FOUND IN THIS PRODUCT COMPLY WITH THE TOXIC  
SUBSTANCES CONTROL ACT INVENTORY REPORTING REQUIREMENTS.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES: NONE

SARA TITLE III SECTION 304 CERCLA SUBSTANCES DANGEREUSES: NONE

SARA TITLE III SECTION 312 HAZARD CLASS:

ACUTE: YES

CHRONIC: NO

FIRE: NO

PRESSURE: NO

REACTIVE: NO

SARA TITLE III SECTION 313 TOXIC CHEMICALS:

COPPER CHLOROPHTHALOCYANINE (12239-87-1)

NOTE:

CHEMICALS ARE LISTED UNDER THE 313 TOXIC CHEMICALS SECTION ONLY IF THEY MEET  
OR EXCEED A REPORTING THRESHOLD.

CALIFORNIA PROPOSITION 65:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED BY THE STATE OF  
CALIFORNIA UNDER THE SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986  
(PROPOSITION 65) AS BEING KNOWN TO CAUSE CANCER, BIRTH DEFECTS OR OTHER  
REPRODUCTIVE HARM: NONE KNOWN



MASSACHUSETTS:

COPPER CHLOROPHTHALOCYANINE (12239-87-1)

SILICA, AMORPHOUS (7631-86-9)

TITANIUM DIOXIDE (13463-67-7)

NEW JERSEY:

COPPER CHLOROPHTHALOCYANINE (12239-87-1)

DIMETHYL SILOXANE, HYDROXY-TERMINATED (70131-67-8)

ETHYLTRIAACETOXSILANE (17689-77-9)

HYDROTREATED MIDDLE PETROLEUM DISTILLATES (64742-46-7)

METHYLTRIAACETOXSILANE (4253-34-3)

POLYDIMETHYLSILOXANE (63148-62-9)

SILICA, AMORPHOUS (7631-86-9)

TETRABENZO-5,10,15,20-DIAZAPORPHYRINEPHTHALOCYANINE [PIGMENT BLUE 15]

(147-14-8)

TITANIUM DIOXIDE (13463-67-7)

PENNSYLVANIA:

COPPER CHLOROPHTHALOCYANINE (12239-87-1)

DIMETHYL SILOXANE, HYDROXY-TERMINATED (70131-67-8)

HYDROTREATED MIDDLE PETROLEUM DISTILLATES (64742-46-7)

POLYDIMETHYLSILOXANE (63148-62-9)

SILICA, AMORPHOUS (7631-86-9)

TITANIUM DIOXIDE (13463-67-7)

-----16. OTHER INFORMATION -----

DISCLAIMER:

THE DATA CONTAINED HEREIN IS BASED UPON INFORMATION THAT ACCUMETRIC LLC BELIEVES TO BE RELIABLE. USERS OF THIS PRODUCT HAVE THE RESPONSIBILITY TO DETERMINE THAT SUITABILITY OF USE AND TO ADOPT ALL NECESSARY PRECAUTIONS TO ENSURE THE SAFETY AND PROTECTION OF PROPERTY AND PERSONS INVOLVED IN SAID USE. ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE INFORMATION, THE HAZARDS CONNECTED WITH THE USE OF THE MATERIAL OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

