

Safety Data Sheet

Supply Co. - SANDABLE GRAY PRIMER, BD14070000

Document Nbr: 075054
Class C Parts IDs BD1407,BD1407-1

S(R*)

SEYMOUR(R*)

SAFETY DATA SHEET

PRINTING DATE: 11/07/2014

REVISED ON: 11/07/2014

-----1 IDENTIFICATION OF THE SUBSTANCE AND MANUFACTURER -----

TRADE NAME: SANDABLE GRAY PRIMER

PRODUCT CODE: BD14070000

PRODUCT CATEGORY: PC9A PAINTS AND COATINGS.

MANUFACTURER/SUPPLIER:

SEYMOUR OF SYCAMORE

917 CROSBY AVENUE

SYCAMORE, IL 60178

PHONE: 815-895-9101

WWW.SEYMOURPAINT.COM

EMERGENCY TELEPHONE NUMBER:

CHEMTEL: 1-800-255-3924, 813-248-0585

IF LOCATED OUTSIDE THE U.S.

-----2 HAZARD(S) IDENTIFICATION -----

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

FLAM. AEROSOL 1:

H222: EXTREMELY FLAMMABLE AEROSOL.

PRESS. GAS:

H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CARC. 2:

H351: SUSPECTED OF CAUSING CANCER.

REPR. 2:

H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

STOT RE 2:

H373: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

EYE IRRIT. 2A:

H319: CAUSES SERIOUS EYE IRRITATION.

STOT SE 3:

H336: MAY CAUSE DROWSINESS OR DIZZINESS.

GHS HAZARD PICTOGRAMS:

GHS02: FLAME

GHS04: GAS CYLINDER

GHS07: EXCLAMATION MARK

GHS08: HEALTH HAZARD

SIGNAL WORD: DANGER

HAZARD STATEMENTS:

EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF CAUSING CANCER.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS:

IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.

KEEP OUT OF REACH OF CHILDREN.

READ LABEL BEFORE USE.

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

WASH HANDS THOROUGHLY AFTER HANDLING.

USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY.

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.

IF EYE IRRITATION PERSISTS:

GET MEDICAL ADVICE/ATTENTION.

STORE LOCKED UP.

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122

DEG. F.

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH
LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS.

-----3 COMPOSITION/INFORMATION ON INGREDIENTS -----

CHEMICAL CHARACTERIZATION: MIXTURES

CHEMICAL DESCRIPTION:

THIS PRODUCT IS A MIXTURE OF THE SUBSTANCES LISTED BELOW WITH NONHAZARDOUS
ADDITIONS.

DANGEROUS COMPONENTS:

67-64-1	ACETONE	34.34%
74-98-6	PROPANE	15.73%
106-97-8	N-BUTANE	9.24%
108-88-3	TOLUENE	6.0%
110-19-0	ISOBUTYL ACETATE	5.95%
64742-47-8	MINERAL SPIRITS	5.82%
13463-67-7	TITANIUM DIOXIDE	4.92%
67-63-0	ISOPROPYL ALCOHOL	2.65%
2807-30-9	GLYCOL ETHER EP	2.11%

-----4 FIRST-AID MEASURES -----

AFTER INHALATION: SUPPLY FRESH AIR; CONSULT DOCTOR IN CASE OF COMPLAINTS.

AFTER SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER.

AFTER EYE CONTACT:

RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. IF SYMPTOMS PERSIST,
CONSULT A DOCTOR.

AFTER SWALLOWING: RINSE MOUTH WITH WATER. DO NOT INDUCE VOMITING.

MOST IMPORTANT SYMPTOMS AND EFFECTS: DIZZINESS

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION NEEDED:

NO FURTHER RELEVANT INFORMATION AVAILABLE.

-----5 FIRE-FIGHTING MEASURES -----

EXTINGUISHING AGENTS:

CO₂, EXTINGUISHING POWDER OR WATER SPRAY. FIGHT LARGER FIRES WITH WATER SPRAY.

SPECIAL HAZARDS: CAN FORM EXPLOSIVE GAS-AIR MIXTURES.

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

A RESPIRATORY PROTECTIVE DEVICE MAY BE NECESSARY.

-----6 ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

USE RESPIRATORY PROTECTIVE DEVICE AGAINST THE EFFECTS OF FUMES/DUST/AEROSOL.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

DISPOSE CONTAMINATED MATERIAL AS WASTE ACCORDING TO SECTION 13.

-----7 HANDLING AND STORAGE -----

PRECAUTIONS FOR SAFE HANDLING: USE ONLY IN WELL VENTILATED AREAS.

STORAGE REQUIREMENTS:

KEEP AWAY FROM SOURCES OF HEAT AND DIRECT SUNLIGHT. DO NOT WAREHOUSE IN

SUBFREEZING CONDITIONS. STORE LOCKED UP.

-----8 EXPOSURE CONTROLS/PERSONAL PROTECTION -----

COMPONENTS WITH LIMIT VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:

67-64-1 ACETONE:

PEL (USA):

LONG-TERM VALUE: 2400 MG/M3, 1000 PPM

REL (USA):

LONG-TERM VALUE: 590 MG/M3, 250 PPM

TLV (USA):

SHORT-TERM VALUE: (1782) NIC-1187 MG/M3, (750) NIC-500 PPM

LONG-TERM VALUE: (1188) NIC-594 MG/M3, (500) NIC-250 PPM

BEI

74-98-6 PROPANE:

PEL (USA):

LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

REL (USA):

LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

TLV (USA): REFER TO APPENDIX F

106-97-8 N-BUTANE:

REL (USA):

LONG-TERM VALUE: 1900 MG/M3, 800 PPM

TLV (USA):

SHORT-TERM VALUE: 2370 MG/M3, 1000 PPM

108-88-3 TOLUENE:

PEL (USA):

LONG-TERM VALUE: 200 PPM

CEILING LIMIT VALUE: 300; 500* PPM

*10-MIN PEAK PER 8-HR SHIFT

REL (USA):

SHORT-TERM VALUE: 560 MG/M3, 150 PPM

LONG-TERM VALUE: 375 MG/M3, 100 PPM

TLV (USA):

LONG-TERM VALUE: 75 MG/M3, 20 PPM

BEI

110-19-0 ISOBUTYL ACETATE:

PEL (USA):

LONG-TERM VALUE: 700 MG/M3, 150 PPM

REL (USA):

LONG-TERM VALUE: 700 MG/M3, 150 PPM

TLV (USA):

LONG-TERM VALUE: 713 MG/M3, 150 PPM

67-63-0 ISOPROPYL ALCOHOL:

PEL (USA):

LONG-TERM VALUE: 980 MG/M3, 400 PPM

REL (USA):

SHORT-TERM VALUE: 1225 MG/M3, 500 PPM

LONG-TERM VALUE: 980 MG/M3, 400 PPM

TLV (USA):

SHORT-TERM VALUE: 984 MG/M3, 400 PPM

LONG-TERM VALUE: 492 MG/M3, 200 PPM

BEI

INGREDIENTS WITH BIOLOGICAL LIMIT VALUES:

67-64-1 ACETONE:

BEI (USA): 50 MG/L

MEDIUM: URINE

TIME: END OF SHIFT

PARAMETER: ACETONE (NONSPECIFIC)

108-88-3 TOLUENE:

BEI (USA):

0.02 MG/L

MEDIUM: BLOOD

TIME: PRIOR TO LAST SHIFT OF WORKWEEK

PARAMETER: TOLUENE

0.03 MG/L

MEDIUM: URINE

TIME: END OF SHIFT

PARAMETER: TOLUENE

0.3 MG/G CREATININE

MEDIUM: URINE

TIME: END OF SHIFT

PARAMETER: O-CRESOL WITH HYDROLYSIS (BACKGROUND)

67-63-0 ISOPROPYL ALCOHOL:

BEI (USA): 40 MG/L

MEDIUM: URINE

TIME: END OF SHIFT AT END OF WORKWEEK

PARAMETER: ACETONE (BACKGROUND, NONSPECIFIC)

HYGIENIC PROTECTION:

IMMEDIATELY REMOVE ALL SOILED AND CONTAMINATED CLOTHING.

WASH HANDS AFTER USE.

AVOID CONTACT WITH THE EYES AND SKIN.

DO NOT EAT OR DRINK WHILE WORKING.

BREATHING EQUIPMENT:

A RESPIRATOR IS GENERALLY NOT NECESSARY WHEN USING THIS PRODUCT OUTDOORS OR IN LARGE OPEN AREAS. IN CASES WHERE SHORT AND/OR LONG TERM OVEREXPOSURE EXISTS, A

CHARCOAL FILTER RESPIRATOR SHOULD BE WORN. IF YOU SUSPECT OVEREXPOSURE
CONDITIONS EXIST, PLEASE CONSULT AN AUTHORITY ON CHEMICAL HYGIENE.

HAND PROTECTION:

PROTECTIVE GLOVES. THE GLOVE MATERIAL MUST BE IMPERMEABLE AND RESISTANT TO THE
SUBSTANCE.

EYE PROTECTION: TIGHTLY SEALED GOGGLES

-----9 PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE: AEROSOL.

ODOR: AROMATIC

ODOR THRESHOLD: NOT DETERMINED.

PH-VALUE: NOT DETERMINED.

MELTING POINT/MELTING RANGE: UNDETERMINED.

BOILING POINT: -110 DEG. C (-166 DEG. F)

FLASH POINT: -19 DEG. C (-2 DEG. F)

FLAMMABILITY (SOLID, GAS): EXTREMELY FLAMMABLE.

DECOMPOSITION TEMPERATURE: NOT DETERMINED.

AUTO IGNITING: PRODUCT IS NOT SELF-IGNITING.

DANGER OF EXPLOSION: IN USE, MAY FORM FLAMMABLE/EXPLOSIVE VAPOUR-AIR MIXTURE.

LOWER EXPLOSION LIMIT: 1.7 VOL %

UPPER EXPLOSION LIMIT: 10.9 VOL %

VAPOR PRESSURE: NOT DETERMINED.

RELATIVE DENSITY: BETWEEN 0.77 AND 0.85 (WATER EQUALS 1.00)

VAPOUR DENSITY: NOT DETERMINED.

EVAPORATION RATE: NOT APPLICABLE.

PARTITION COEFFICIENT N-OCTONAL/WATER: NOT DETERMINED.

SOLUBILITY: NOT DETERMINED.

VISCOSITY: NOT DETERMINED.

VOC CONTENT: 586.2 G/L / 4.89 LB/GL

VOC CONTENT (LESS EXEMPT SOLVENTS): 49.8%

MIR VALUE: 0.86

SOLIDS CONTENT: 15.8%

-----10 STABILITY AND REACTIVITY -----

REACTIVITY: STABLE AT NORMAL TEMPERATURES.

CONDITIONS TO AVOID:

DO NOT ALLOW CAN TO EXCEED 120 DEGREES FAHRENHEIT. DO NOT WAREHOUSE IN
SUBFREEZING TEMPERATURES.

CHEMICAL STABILITY: NOT FULLY EVALUATED.

POSSIBILITY OF HAZARDOUS REACTIONS: NO DANGEROUS REACTIONS KNOWN.

INCOMPATIBLE MATERIALS: NO FURTHER RELEVANT INFORMATION AVAILABLE.

HAZARDOUS DECOMPOSITION: NO DANGEROUS DECOMPOSITION PRODUCTS KNOWN.

-----11 TOXICOLOGICAL INFORMATION -----

LD/LC50 VALUES THAT ARE RELEVANT FOR CLASSIFICATION:

106-97-8 N-BUTANE:

INHALATIVE LC50/4 H: 658 MG/L (RAT)

110-19-0 ISOBUTYL ACETATE:

ORAL LD50: 4763 MG/KG (RBT)

13463-67-7 TITANIUM DIOXIDE:

ORAL LD50: >20000 MG/KG (RAT)

DERMAL LD50: >10000 MG/KG (RBT)

INHALATIVE LC50/4 H: >6.82 MG/L (RAT)

67-63-0 ISOPROPYL ALCOHOL :

ORAL LD50: 4570 MG/KG (RAT)

DERMAL LD50: 13400 MG/KG (RAB)

INHALATIVE LC50/4 H: 30 MG/L (RAT)

INFORMATION ON TOXICOLOGICAL EFFECTS: NO DATA AVAILABLE.

SENSITIZATION: NO SENSITIZING EFFECTS KNOWN.

CARCINOGENIC CATEGORIES:

IARC (INTERNATIONAL AGENCY FOR RESEARCH ON CANCER):

108-88-3 TOLUENE 3

13463-67-7 TITANIUM DIOXIDE 2B

67-63-0 ISOPROPYL ALCOHOL 3

NTP (NATIONAL TOXICOLOGY PROGRAM): NONE OF THE INGREDIENTS IS LISTED.

-----12 ECOLOGICAL INFORMATION -----

AQUATIC TOXICITY: HAZARDOUS FOR WATER, DO NOT EMPTY INTO DRAINS.

PERSISTENCE AND DEGRADABILITY:

THE PRODUCT IS DEGRADABLE AFTER PROLONGED EXPOSURE TO NATURAL WEATHERING PROCESSES.

BIOACCUMULATIVE POTENTIAL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

MOBILITY IN SOIL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

OTHER ADVERSE EFFECTS: NO FURTHER RELEVANT INFORMATION AVAILABLE.

-----13 DISPOSAL CONSIDERATIONS -----

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR COMPACT. PARTIALLY EMPTY CANS MUST BE DISPOSED OF RESPONSIBLY. DO NOT HEAT OR CUT EMPTY CONTAINERS WITH ELECTRIC OR GAS TORCHES.

RECOMMENDATION: COMPLETELY EMPTY CANS SHOULD BE RECYCLED.

-----14 TRANSPORT INFORMATION -----

UN-NUMBER: UN1950

DOT: AEROSOLS, FLAMMABLE

ADR: 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

MARINE POLLUTANT:

YES

SYMBOL (FISH AND TREE)

SPECIAL MARKING (ADR): SYMBOL (FISH AND TREE)

SPECIAL PRECAUTIONS FOR USER:

WARNING: GASES

EMS NUMBER: F-D, S-U

QUANTITY LIMITATIONS:

ON PASSENGER AIRCRAFT/RAIL: 75 KG

ON CARGO AIRCRAFT ONLY: 150 KG

ADR:

EXCEPTED QUANTITIES (EQ):

CODE: E0

NOT PERMITTED AS EXCEPTED QUANTITY

IMDG:

LIMITED QUANTITIES (LQ): 1L

EXCEPTED QUANTITIES (EQ):

CODE: E0

NOT PERMITTED AS EXCEPTED QUANTITY

PACKAGING GROUP:

UN "MODEL REGULATION": UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

-----15 REGULATORY INFORMATION -----

SARA SECTION 355 (EXTREMELY HAZARDOUS SUBSTANCES):

NONE OF THE INGREDIENTS IN THIS PRODUCT ARE LISTED.

SARA SECTION 313 (SPECIFIC TOXIC CHEMICAL LISTINGS):

108-88-3 TOLUENE

7779-90-0 TRIZINC BIS(ORTHOPHOSPHATE)

67-63-0 ISOPROPYL ALCOHOL

CPSC:

THIS PRODUCT COMPLIES WITH 16 CFR 1303 AND DOES NOT CONTAIN MORE THAN 90 PPM OF
LEAD.

CALIFORNIA PROPOSITION 65 CHEMICALS KNOWN TO CAUSE CANCER:

13463-67-7 TITANIUM DIOXIDE

100-41-4 ETHYL BENZENE

1333-86-4 CARBON BLACK

CALIFORNIA PROPOSITION 65 CHEMICALS KNOWN TO CAUSE DEVELOPMENTAL TOXICITY:

108-88-3 TOLUENE

CANADIAN ENVIRONMENTAL PROTECTION ACT:

ALL HAZARDOUS INGREDIENTS FOR THIS PRODUCT APPEAR ON THE CANADIAN DOMESTIC
SUBSTANCE LIST.

EPA:

67-64-1 ACETONE I

108-88-3 TOLUENE II

110-19-0 ISOBUTYL ACETATE D

7779-90-0 TRIZINC BIS(ORTHOPHOSPHATE) D, I, II

-----16 OTHER INFORMATION -----

CONTACT: REGULATORY AFFAIRS

DATE OF PREPARATION / LAST REVISION: 11/07/2014